

### BIRM

Tank Diameter	Flow Rate	Backwash Rate
8"	1.5	4
9"	1.9	5
10"	2.3	6
12"	3.3	7
13"	3.9	10

### CALCITE

Tank Diameter	Flow Rate	Backwash Rate
8"	1.4	4
9"	1.8	5
10"	2.2	6
12"	3.1	7
13"	3.7	10

### FILTER AG

Tank Diameter	Flow Rate	Backwash Rate
8"	1.7	3
9"	2.2	4
10"	2.7	5
12"	3.9	7
13"	4.6	9

### GRANULAR ACTIVATED CARBON

Tank Diameter	Flow Rate	Backwash Rate
8"	1.75	3
9"	2.3	4
10"	2.8	5
12"	4	6
13"	4.5	7

### MANGANESE GREENSAND

Tank Diameter	Flow Rate	Backwash Rate
8"	1.2	4
9"	1.5	6
10"	1.9	7
12"	2.7	9
13"	3.2	12

### MULTIMEDIA

Tank Diameter	Flow Rate	Backwash Rate
8"	3.5	4
9"	4.4	5
10"	5.4	6
12"	7.9	7
13"	9.2	10

### KATALOX LITE

Tank Diameter	Flow Rate	Backwash Rate
8"	3.2	4
9"	4	5
10"	5	7
12"	7	10
13"	8.3	8.3