

## SS/SSH Series Submersible Pumps

The SS/SSH series are built with rugged precision to work under the toughest conditions yet provide years of superior performance.



5SS05-2W115-NC

<b>5</b>	<b>SS</b>	<b>05</b>	<b>2W</b>	<b>115</b>	<b>NC</b>
GPM	Super Stainless	Motor HP	Wires	Volts	No Control Box

50SSH15-3W230-NC

<b>50</b>	<b>SSH</b>	<b>15</b>	<b>3W</b>	<b>230</b>	<b>NC</b>
GPM	SS High Flow	Motor HP	Wires	Volts	No Control Box

### READING THE MODEL NUMBER

Gallons Per Minute	5GPM, 8GPM, 12GPM, 20GPM, 35GPM, 50GPM, 80GPM
Pump Type	Super Stainless (SS) or Super Stainless High Flow (SSH - 35GPM and Higher)
Motor Horsepower	.5HP, .75HP, 1HP, 1.5HP, 2HP, 3HP, 5HP
Wires	2 Wires or 3 Wires
Volts	115V or 230V
Control Box	3 Wire Pumps come with a control box - For pump & motor only, look for "NC" code

PART	MATERIAL
Check Valve	304 SS (Stainless Steel) external check valve with 1.25" FNPT connection 35GPM+ models use an integral check valve with a 2" FNPT connection
Discharge Head / Motor Bracket	304 SS, fits any standard 4" submersible motor
Shaft	Hexagonal 303 SS shaft
Couplings	Made of stainless steel and fit perfectly to any 4" standard motor which allows maximum efficiency
Diffuser	Injection molded Noryl
Impeller	Rugged injection molded polycarbonate
Disc	Made of stainless steel
Top Bearing	Injection molded fiber reinforced polypropylene with a rubber center for an extremely precise shaft alignment and improved sand handling capability
Housing	304 SS – Threaded for field serviceability
Fasteners	All stainless steel fasteners
Motor	Pentek XE , 2 and 3 wire motor options