





# WELLXTROL

## Next Generation Well Tanks Featuring Antimicrobial Protection

### Specifications



WX-101 through WX-200



WX-201 through WX-350

Model Number	Tank Volume (Gallons)	Max. Acceptance Factor	Dimensions		System Conn. (Inches)	Drawdown (Gallons)			Shipping Weight (lbs.)
			A Diameter (Inches)	B Height (Inches)		30/50	40/60	50/70	
WX-101	2.0	0.45	8	13	¼ NPTM	0.6	0.6	0.5	5
WX-102	4.4	0.55	11	15	¼ NPTM	1.4	1.2	1.0	9
WX-103	7.6	0.43	11	22	¼ NPTM	2.4	2.0	1.8	15
WX-104	10.3	1.00	15	18	1 NPTM	3.2	2.8	2.4	20
WX-200	14.0	0.81	15	22	1 NPTM	4.3	3.8	3.3	22
WX-201	14.0	0.81	15	25	1 NPTF	4.3	3.8	3.3	25
WX-202	20.0	0.57	15	32	1 NPTF	6.2	5.4	4.7	33
WX-202XL	26.0	0.44	15	39	1 NPTF	8.0	7.0	6.1	36
WX-203	32.0	0.35	15	47	1 NPTF	9.9	8.6	7.6	43
WX-205	34.0	1.00	22	30	1 ¼ NPTF	10.5	9.1	8.0	61
WX-250	44.0	0.77	22	36	1 ¼ NPTF	13.6	11.8	10.4	69
WX-251	62.0	0.55	22	47	1 ¼ NPTF	19.2	16.6	14.6	92
WX-255	81.0	0.41	22	57	1 ¼ NPTF	25.0	21.7	19.1	103
WX-252	86.0	0.39	22	62	1 ¼ NPTF	26.6	23.0	20.3	114
WX-302	86.0	0.54	26	47	1 ¼ NPTF	26.6	23.0	20.3	123
WX-350	119.0	0.39	26	62	1 ¼ NPTF	36.8	31.9	28.1	166

Stainless Steel System Connection.

Maximum Working Pressure: All models except WX-252: 150 psig. WX-252: 100 psig. Factory Precharge: 38 psig.

Drawdown can be affected by various ambient and system conditions, including temperature and pressure.

# Quick Sizing Chart

Pump Discharge Rate (Approx. GPM)	OPERATING PRESSURE					
	30/50 PSIG		40/60 PSIG		50/70 PSIG	
	ESP I	ESP II	ESP I	ESP II	ESP I	ESP II
5	WX-202	WX-205	WX-202	WX-205	WX-202	WX-250
7	WX-202XL	WX-250	WX-203	WX-251	WX-203	WX-251
10	WX-205	WX-251	WX-205	WX-255	WX-250	WX-302
12	WX-250	WX-255	WX-250	WX-255	WX-251	WX-350
15	WX-250	WX-302	WX-251	WX-350	WX-251	WX-350
20	WX-251	WX-350	WX-255	WX-255 (2)	WX-302	WX-302 (2)
25	WX-255	WX-255 (2)	WX-302	WX-302 (2)	WX-350	WX-350 (2)
30	WX-302	WX-302 (2)	WX-350	WX-350 (2)	WX-350	WX-302 (3)
35	WX-350	WX-350 (2)	WX-350	WX-350 (2)	WX-255 (2)	WX-350 (3)
40	WX-350	WX-350 (2)	WX-255 (2)	WX-302 (3)	WX-302 (2)	WX-350 (3)

ESP I - Effective Sizing Protection I: The tank selection is based on approximately one minute running time. This is recommended for pumps up to 3/4 hp.

ESP II - Effective Sizing Protection II: The tank selection is based on approximately two minutes running time. This is recommended for pumps 3/4 hp or larger.

